

# CPS 3-AXLE BOTTOM DUMP TRAILER [25] Omanac

#### SPECIFICATIONS

- Model 4B340A200
- 40' OAL
- 96" Width
- · Height: 10' w/Bangboards
- 23 CU YD Capacity
- Est Weight: 13,723 LBS

#### **ELECTRICAL**

- DOT Approved LED Lighting System
- Amber Mid-Flashers
- Front Connector: 7-Way (SAE J560)
- Additional Front 6-Way Connector for Gate Control
- Rear 7-Way & 6-Way Connector for Pup Control

#### FRAME GATES, & HOPPER

- 12" Wood Bangboards
- 18" AR450 Steel Wings
- Steel Front & Rear Fenders
- Hopper: 10 & 12GA (Standard Lightweight)
- AR400 Steel Gates w/ Slide Locks
- Oscillating Fifth Wheel w/King Pin
- King Pin Location: 18" (Standard)
- Pintle Hook Installed Under Push Block
- Drop Legs/Stiff Leg 4" X 4" Square
- · Removeable Push Block
- Tarp Brackets Installed for Cramaro Flip Tarp (Available Upon Request)

#### **PAINT & SAFETY**

- Painted White
- Epoxy Primer w/Polyurethane Topcoat.
- Reflective Tape Conspicuity Striping

## **UNDERCARRIAGE**

- 3-Axles (Tridem)
- Hub Piloted 25k Axles: 1ABS 1 Non-ABS
- Spring Suspension
- Standard Galvanized Windrow Deflector
- 16 1/2" X 7" Cam Brakes
- HM 218248 & HM 212049 Bearings
- Meritor, Automatic Slack Adjusters
- Stemco Seals
- Tire Size: 385/65R22.5-14.9 W X 41.9 DI
- Outside Wheels: Aluminum

### **AIR SYSTEM**

- Twin 8" Cylinders w/60 Gal Air Tank, Oiler, Filter, & Quick Release
- Electric Cab Gate Controls
- Manual Gate Hand Controls from Ground
- Relay Valve Installed on Tank
- Quick Release Valve on Emergency Line







