

WESTERN TRUCK & TRAILER SALES INC.

Sales, Finance & Rentals

1885 South 900 West
Salt Lake City, UT 84104

(800) 869-4121

Parts & Service

1490 South 400 West
Salt Lake City, UT 84115

PARTS
WesternTruck.com

ONLINE



CPS UTAH BOTTOM DUMP TRAIN 3-4



SPECIFICATIONS

- 3-Axle Lead:
Model 4B340A200
- 4-Axle Pup:
Model 4B224A200
- 37 CU YD Capacity
- 64' OAL
- 96" Wide
- Hopper Height: 10'
w/Bangboards
- Est Weight: 29,200 LBS

ELECTRICAL

- DOT Approved LED Lighting System
- Amber Mid-Flashers
- Front Connector: 7-Way (SAE J560)
- Additional Front 6-Way Connector for Gate Control
- Rear 7-Way & 6-Way Connector for Pup (Lead)

FRAME & TUB

- 3-Axle Lead 40' OAL
 - Oscillating Fifth Wheel w/King Pin
 - King Pin Location: 18" (Standard)
 - Pintle Hook Installed Under Push Block
 - Drop Legs/Stiff Leg 4" X 4" Square
- 4-Axle Pup 24' OAL
 - Permanently Mounted Turntable w/Tandem Axle Dolly
 - Adjustable Draw Bar, 8'-12'; 12' Increments
 - 3" ID Pintle Eye
 - Dolly Jack
 - Aluminum Shed Plates at Front & Back
- 12" Wood Bangboards
- 18" AR450 Steel Wings
- Steel Front & Rear Fenders
- Hopper: 10 & 12GA (Standard Lightweight)
- AR400 Steel Gates w/ Side Locks
- Removeable Push Block
- Tarp Brackets Installed for Cramaro Flip Tarp (Available Upon Request)

UNDERCARRIAGE

- Hub Piloted 25k Axles: 1ABS 1 Non-ABS
- Spring Suspension
- Standard Galvanized Windrow Deflector
- 16 1/2" X 7" Cam Brakes
- HM 218248 & HM 212049 Bearings
- Meritor, Automatic Slack Adjusters
- Stemco Seals
- Tire Size: 385/65R22.5-14.9 W X 41.9 DI
- Outside Wheels: Aluminum

AIR SYSTEM

- Twin 8" Cylinders w/60 Gal Air Tank, Oiler, Filter, & Quick Release
- Electric Cab Gate Controls
- Manual Gate Hand Controls from Ground
- Relay Valve Installed on Tank
- Quick Release Valve on Emergency Line

PAINT & SAFETY

- Painted White
- Epoxy Primer w/Polyurethane Topcoat.
- Reflective Tape Conspicuity Striping

