Sales, Finance & Rentals 1885 South 900 West Salt Lake City, UT 84104

(800) 869-4121

Parts & Service 1490 South 400 West Salt Lake City, UT 84115



XL SPECIALIZED XL 110 LOW-PROFILE HDG: With Motor

DIMENSIONS:

- 110,000 LB Capacity
- 53' OAL
- 108" Wide

MAIN DECK

- 25' Long
- T-1 Flange, 80K Web
- (4) 16" Fabricated I-Beams
- 24" Loaded Deck Height
- 8" Ground Clearance
- 10" & 4" Stubbed Jr. I-Beams, Alternating Centers
- 31" Front Flip Ramps
- 7 Bent D-Rings Per Side
- 1 3/4" Apitong Decking Raised, Open Center
- Toolbox in Front of Deck
- 4 Flat D-Rings in Toolbox
- 13 Chain Drops per Side
- Heavy-Duty Swing Out Outriggers on 24" Centers
- Heavy-Duty Flatback Outriggers, Front and Center
- 2 Flag Holders
- Bucket Well at Rear, Plate on Bottom
- 4 Flat D-Rings in Bucket Well
- Front Ramp Upper Flange Reinforcement

GOOSENECK

- 13' Low-Profile Style Neck with Relief Cut-Out
- 13HP Honda Unit in Neck Base w/Steel Cover &
- **Dual Hydraulics**
- 51" 5th Wheel Height
- 5 Position Variable Ride Height
- 110" & 84" Swing Clearance
- 16" & 42" King Pin Setting
- Hydraulics Run Off Wet Kit
- Air Operated Lock with Manual Safety Latch

Work Light

REAR BRIDGE

- 15' Long
- Rear Transition with 32° Slope
- 40" Loaded Deck Height
- Open Wheels Bolster Style
- Covered Boom Trough Bolt-on **Bottom Plate**
- 2 Flat D-Rings on Rear Main Beams
- 2 Chain Drops on Each Bolster
- 2 Flag Holders
- 2 Stake Pockets in Tail Channel
- Frame Reinforcement For Booster

SUSPENSION

- 25,000 LB Air Ride
- Raise And Lower Valve
- Manual Ride Height Control
- Liquid Filled Air Gauge

WHEELS & TIRES

- 8.25 X 22.5 Steel Rims
- 255 / 70R / 22.5 H-Rated Tires

AXLES

- (3) 25,000 LB Nominal
- Air Lift On 3rd Axle
- Hub Pilot, Outboard Drums
- 16 1/2" X 7" Brakes
- Auto Slack Adjusters
- 60" Axle Spacing
- Limit Chains On All Axles
- Spring Brakes 1 Axle

MISC.

- 4" Amber Strobe Tail Light
- Painted Black
- Warranty: 5-Yr Structural, 1-Yr Paint







